



## Product Specification **6605-10**

Taconic 6605-10 is a woven fiberglass cloth tape complete with silicone adhesive (slightly thicker than the standard 6605-07). This pressure sensitive tape is rated class "H" as an insulator. This tape is as a UL approved electrical insulation tape used for small motor rewind applications, transformer insulation, and cable splicing. This tape is produced self wound (No Liner). Maximum width is 42" wide.

Product Properties	Units	Value	Tolerance	Test Method
Adhesive Type		<b>SILICONE</b>		
Substrate Type		<b>E-GLASS</b>		
Total Weight of Substrate	lbs/yd <sup>2</sup>	<b>0.245</b>		
% Coating of Substrate		<b>N/A</b>		
Substrate Thickness	inch	<b>0.005</b>		ASTM D3652
Adhesive Thickness	inch	<b>0.004</b>		ASTM D3652
Total Product Thickness	inch	<b>0.009</b>		ASTM D3652
Adhesive Strength	oz/in	<b>30</b>	Typical	ASTM D3330 METHOD A
		<b>20</b>	Minimum	
Adhesive Shelf Life	Months	<b>12</b>	From DOM	
Operating Temperature	°FAHRENHEIT	<b>-100° to +500°</b>		

**Storage conditions for all Tapes: Temperature -23 C +/- 4 C (66.2F~80.6F) and Relative Humidity- 50% +/- 10%**

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Please contact us for samples or a quotation

### Taconic Headquarters

Petersburgh, NY

[www.4taconic.com](http://www.4taconic.com)  
[info@4taconic.com](mailto:info@4taconic.com)



### Western US, Mexico & Central America

La Verne, CA

[www.4taconic.com](http://www.4taconic.com)  
[info@4taconic.com](mailto:info@4taconic.com)

For queries in Europe please visit [www.taconic-ipd.com](http://www.taconic-ipd.com)  
or email [info@taconic-ipd.com](mailto:info@taconic-ipd.com)

### Canada

Mississauga, CAN

[www.4taconic.com](http://www.4taconic.com)  
[info@4taconic.com](mailto:info@4taconic.com)

